Environmental Protection Agency

(b) Chlorinator Wet Air Pollution Control.

PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of chlorinated	
Arsenic Lead Zinc Fluoride	27.530 5.531 19.230 461.000	12.250 2.634 8.034 262.100

(c) Germanium Hydrolysis Filtrate.

PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of hydrolyzed	
ArsenicLeadZincFluoride	39.440 7.925 27.550 660.500	17.550 3.774 11.510 375.500

(d) Acid Wash and Rinse Water.

PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per/millior pounds of germanium washed	
ArsenicLeadZincFluoride	325.50 65.40 227.40 5,450.00	144.80 31.14 94.99 3,099.00

(e) Gallium Hydrolysis Filtrate.

PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of gallium hydrolyzed	
ArsenicLeadZincFluoride	70.450 14.160 49.220 1,180.000	31.350 6.742 20.560 670.800

(f) Solvent Extraction Raffinate.

PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of gallium produced by solvent extraction	
ArsenicLeadZincFluoride	39.330 7.904 27.480 658.700	17.500 3.764 11.480 374.500

§ 421.187 [Reserved]

Subpart Q—Secondary Indium Subcategory

Source: 50 FR 38353, Sept. 20, 1985, unless otherwise noted.

§ 421.190 Applicability: Description of the secondary indium subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of indium at secondary indium facilities processing spent electrolyte solutions and scrap indium metal raw materials.

§ 421.191 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§§ 421.192-421.193 [Reserved]

§ 421.194 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Displacement Supernatant.

NSPS FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millic pounds) of indium met produced	
Cadmium	2.105	0.929
Lead	2.600	1.238
Zinc	9.037	3.776
Indium	2,724	1.114

§421.195

NSPS FOR THE SECONDARY INDIUM SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Total suspended solidspH	253.800 (¹)	120.700 (¹)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Spent Electrolyte.

NSPS FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ls per million cathode indium
Cadmium	12.170	5.370
Lead	15.040	7.160
Zinc	52.270	21.840
Indium	15.750	6.444
Total suspended solids	1,468.000	698.100
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

§ 421.195 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources. The mass of wastewater pollutants in secondary indium process wastewater introduced into a POTW must not exceed the following values:

(a) Displacement Supernatant.

PSES FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million indium metal
Cadmium Lead Zinc Indium	2.105 2.600 9.037 2.724	0.929 1.238 3.776 1.114

(b) Spent Electrolyte.

40 CFR Ch. I (7-1-00 Edition)

PSES FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million cathode in- ced
Cadmium	12.170	5.370
Lead	15.040	7.160
Zinc	52.270	21.840
Indium	15.750	6.444

§ 421.196 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of wastewater pollutants in secondary indium process wastewater introduced into a POTW should not exceed the following values:

(a) Displacement Supernatant.

PSNS FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of indium metal produced	
Cadimum	2.105	0.929
Lead	2.600	1.238
Zinc	9.037	3.776
Indium	2.724	1.114

(b) Spent Electrolyte.

PSNS FOR THE SECONDARY INDIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode indium produced	
Cadmium	12.170 15.040	5.370 7.160
Zinc	52.270	21.840
Indium	15.750	6.444